

TEST SHEET

NR. LSF/NC12931/00000/3/CH

Oltrona di S. Mamette, 01.04.2008

British Standard 5852:1990

Section 4: Source 5

THE REQUIRING FIRM

ICF SpA

via Cassanese, 108

I - 20060 Vignate (MI)

DENOMINATION AND DESCRIPTION OF THE MATERIAL :

UNA EXECUTIVE CHAIR PELLE

Covering: Compell HELL

Interliner: ORV VALFORM

Foam: Olmo ELAST 50/65 (back/seat)

Note: The water soaking procedure wasn't carried out on the cover. Conditioned samples.

TEST RESULTS: Source 5:

Ignition source CRIB 5									
Type of test rig:				Large test rig					
Duration of				Extent of damage of horizontal component			Extent of damage of vertical component		
Ignition (y/n)	Ignition source (min.sec)	Flames (min.sec)	Smoke (min.sec)	Width (mm)	Length (mm)	Depth (mm)	Height (mm)	Length (mm)	Depth (mm)
yes	00.48	03.10	07.16	90	60	20	250	50	20
yes	00.37	02.42	06.45	80	60	20	230	100	20

Mass loss test 1: 18 g

Mass loss test 2: 31,8 g

As a consequence of the above results, the examined material is to consider

positive

The global result is:

section 4: I/5

The above test results relate only to the ignitability of the combination of materials under the particular conditions of test; they are not intended as a means of assessing the full potential fire hazard of the materials in use.
Report valid only for internal using.

LSF PRESIDENT
HEAD OF RESEARCH TEAM

-Silvio Messa-

SUBSTITUTIVE DIRECTOR

-Maddalena Pezzani-

TEST OPERATOR

-Silvana Carnevale-